



## Enabler 2R-HV

### BJ-235

Control up to two lights, doors or other elements

Enabler 2R-HV is a device with **two switched relay contacts** that allows you to **control two different elements** of your environment or **two different functions** of the same element.

It can be activated remotely via **any of [our controllers](#)** or manually by means of wall switches.

Use it to control electrical appliances such as lights, doors, recessed plugs or others. It must be powered at 230 VAC.

Choose from four operating modes: latched, dead man, combined and 1-second pulse.

This device is part of our [environmental control](#) solution.

- Power supply: 230VAC.
- Controllable remotely using our remotes or manually by means of wall switches.
- Size: 150 x 59 x 36 mm.
- Radio Frequency: 433 MHz.
- Connect up to 16 different Enabler 2R in the same system.
- Four operating modes selected with the jumpers: latched, dead man, combined and 1 second pulse .
- In combined mode, the operating mode depends on the length of the click:

- Short click: latched (auto-off at 55 seconds) .
- Long click: dead man.

- Control input terminal for manual control.
- Maximum load:

- Inductive loads: 3.5A/350W/cosφ=0.4.
- Compensated fluorescents: 100W.
- Halogen lamps with transformer: 2,8A/500W/cosφ=0,76.

Compatible with wall switch.

